

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Identification of the substance or preparation**

**Megol Motorenöl Mobility 5W-30 1 L  
 Art.-Nr. 3185**

**Use of the substance/preparation**

Motor oil

**Company/undertaking identification**

Meguïn GmbH & Co. KG Mineraloelwerke, Rodener Straße 25, D -66740 Saarlouis  
 Telephone 06831/89 09-0, Fax 06831/89 09-62

E-mail address of the competent person: info@chemical-check.de, k.schnurbusch@chemical-check.de

**Emergency telephone**

**Advisory office in case of poisoning:**

Tel.:

---

**Telephone number of the company in case of emergencies:**

Tel. 08.00h - 17.00h 06831/8909-65 17.00h - 08.00h 06831/8909-16

### 2. HAZARDS IDENTIFICATION

Preparation is not classified as hazardous in the sense of directive 1999/45/EC.

**To people**

See point 11 and 15.

Not applicable

**To the environment**

See point 12.

Product can compose a film on the water surface, which can prevent oxygen exchange.

Hazardous to drinking water, on escape of even small quantities.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name			
content %	Symbol Registration number (ECHA)	R-phrases Classification categories / Indications of danger:	EINECS, ELINCS
Styrene hydrocarbon polymer			
1 - 5		53 Dangerous for the environment	

For complete wording of the R-phrases / H-phrases (GHS/CLP), refer to point 16.

### 4. FIRST AID MEASURES

**4.1 Inhalation**

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

**4.2 Skin contact**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision: 21.06.2010 Replaces the version of: 13.07.2009 PDF date: 21.06.2010  
Megol Motorenöl Mobility 5W-30 1 L Art.-Nr. 3185

Wash thoroughly with soap and copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

#### **4.2 Eye contact**

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### **4.4 Ingestion**

Rinse the mouth thoroughly with water.

Call doctor immediately - have Data Sheet available.

#### **4.5 Special resources necessary for first aid**

n.c.

## **5. FIRE-FIGHTING MEASURES**

### **5.1 Suitable extinguishing media**

CO2

Foam

Dry extinguisher

Large fire:

Water jet spray / alcohol resistant foam

Cool container at risk with water.

### **5.2 Extinguishing media which shall not be used for safety reasons**

High volume water jet

### **5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases**

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Oxides of phosphorus

Toxic pyrolysis products.

Hot product gives off combustible vapours.

### **5.4 Special protective equipment for fire-fighters**

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary

### **5.5 Further information**

Dispose of contaminated extinction water according to official regulations.

## **6. ACCIDENTAL RELEASE MEASURES**

Refer to point 13. and for personal protection refer to point 8.

### **6.1 Personal precautions**

Avoid formation of oil mist.

Remove possible causes of ignition - do not smoke.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping

### **6.2 Environmental precautions**

If leakage occurs, dam up.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

### **6.3 Methods for cleaning up**

Collect using absorbant material (e.g. Universal binding medium, sand, kieselguhr) and dispose of according to point 13.

Oil binder

## **7. HANDLING AND STORAGE**

### **7.1 Handling**

#### **Tips for safe handling:**

See point 6.1

Avoid formation of oil mist.

Avoid contact with eyes.

Avoid long lasting or intensive contact with skin.  
 Do not heat to temperatures close to flash point.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Do not carry cleaning cloths soaked in product in trouser pockets.  
 Observe directions on label and instructions for use.

## 7.2. Storage

### Requirements for storage rooms and containers:

Not to be stored in gangways or stair wells.  
 Store product closed and only in original packing.

### Special storage conditions:

See point 10  
 Protect against moisture and store closed.  
 Store at room temperature.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Exposure limit values

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m <sup>3</sup> (ACGIH)	WEL-STEL: 10 mg/m <sup>3</sup> (ACGIH)	---
BMGV: ---	Other information: ---	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

## 8.2 Exposure controls

### 8.2.1 Occupational exposure controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Respiratory protection:  
 Normally not necessary.  
 With oil mist formation:  
 Filter A2 P2 (EN 14387)  
 Observe wearing time limitations for respiratory protection equipment.  
 Hand protection:  
 Protective gloves, oil resistant (EN 374)  
 If applicable  
 Protective nitrile gloves (EN 374)  
 Protective Neopren gloves (EN 374).  
 Protective PVC gloves (EN 374)  
 Protective hand cream recommended.  
 Eye protection:  
 Tight fitting protective goggles with side protection (EN 166).  
 Skin protection:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Additional information on hand protection - No tests have been performed.  
 Selection made for preparations according to the best available knowledge and information on the ingredients.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of preparations the resistance of glove materials cannot be calculated in advance

so it has to be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.2 Environmental exposure controls

n.av.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 General information

Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic

### 9.2. Important health, safety and environmental information

10 % pH-value:	n.av.
Boiling point/boiling range (°C):	n.av.
Melting point/melting range (°C):	- 36
Flash point (°C):	230
Autoflammability:	n.c.
Minimum limit of explosion:	n.a.
Maximum limit of explosion:	n.a.
Vapour pressure:	n.c.
Density (g/ml):	0,855
Water solubility:	Insoluble
Viscosity:	66 mm <sup>2</sup> /s (40°C), 11,6 mm <sup>2</sup> /s (100°C)

## 10. STABILITY AND REACTIVITY

### Conditions to avoid

See point 7  
 Stable when handled and stored correctly.  
 Protect from humidity.  
 Open flame, ignition sources

### Materials to avoid

See point 7  
 Avoid contact with strong oxidizing agents.

### Hazardous decomposition products

See point 5.3  
 No decomposition when used as directed.

## 11. TOXICOLOGICAL INFORMATION

### Acute toxicity and immediate effects

Ingestion, LD50 rat oral (mg/kg):	n.av.
Inhalation, LC50 rat inhal.(mg/l/4h):	n.av.
Skin contact, LD50 rat dermal (mg/kg):	n.av.
Eye contact:	n.av.

### Delayed and chronic effects

Sensitization:	n.c.
Carcinogenicity:	n.c.
Mutagenicity:	n.c.
Reproductive toxicity:	n.c.
Narcosis:	n.c.

### Further information

The product was not tested.  
 Classification according to calculation procedure.  
 The following may occur:  
 Irritation of the eyes  
 With long-term contact:  
 Drying of the skin.  
 Dermatitis (skin inflammation)  
 With oil mist formation:  
 Irritation of the respiratory tract

## 12. ECOLOGICAL INFORMATION

The product was not tested.	
Persistence and degradability:	n.av.
Behaviour in sewage plants:	Isolate as much as possible with an oil separator.
Aquatic toxicity:	n.av.
Ecological toxicity:	n.av.
Mobility:	n.av.
Accumulation:	Possible
Results of PBT assessment	
n.av.	
Other adverse effects:	n.av.

## 13. DISPOSAL CONSIDERATIONS

### 13.1. for the material / preparation / residue

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.  
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.  
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Pay attention to local and national official regulations  
 Implement substance recycling.  
 E.g. suitable incineration plant.

Observe regulations for disposal of old oil/waste.

### 13.2 for contaminated packing material

See point 13.1

Pay attention to local and national official regulations

Empty container completely.

Untamminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging

## 14. TRANSPORT INFORMATION

### General statements

UN-Number: n.a.

### Road/Rail-transport (ADR/RID)

Class/packing group: n.a.

Classification code: n.a.

LQ: n.a.

Tunnel restriction code:

### Transport by sea

IMDG-code: n.a. (class/packing group)

Marine Pollutant: n.a.

### Transport by air

IATA: n.a. (class/secondary danger/packing group)

### Additional information:

Non-dangerous material according to Transport Regulations.

## 15. REGULATORY INFORMATION

**Classification according to Dangerous Product Regulations incl. EC Directives (67/548/EEC and 1999/45/EC)**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision: 21.06.2010 Replaces the version of: 13.07.2009 PDF date: 21.06.2010  
 Megol Motorenöl Mobility 5W-30 1 L Art.-Nr. 3185

Symbols:	Not applicable
Indications of danger:	---
R-phrases:	
S-phrases:	
Additions:	
Safety data sheet available for professional user on request.	
Observe restrictions:	n.a.

## 16. OTHER INFORMATION

These details refer to the product as it is delivered.

Storage class VCI (Germany):	10
Revised points:	3, 8, 13

The following phrases represent the prescribed R-phrases / H-phrases (GHS/CLP) for the ingredients (designated in point 3).  
 53 May cause long-term adverse effects in the aquatic environment.

### Legend:

n.a. = not applicable / n.v., k.D.v. = n.av. = not available / n.g. = n.c. = not checked  
 WEL = Workplace Exposure Limit EH40, TWA = Long-term exposure limit (8-hour TWA (= time weighted average) reference period), STEL = Short-term exposure limit (15-minute reference period) / BMGV = Biological monitoring guidance value EH40  
 AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany) / BGW = "Biologischer Grenzwert" (biological limit value, Germany)  
 VbF = Regulations for flammable liquids (Austria)  
 WGK = water hazard class (Germany) - WGK 3 = very hazardous, WGK 2 = hazardous, WGK 1 = slightly hazardous to water  
 VOC = Volatile organic compounds / AOX = Adsorbable organic halogen compounds  
 VwVwS = Administrative Order relating to substances hazardous to water (Germany)  
 The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.  
 No responsibility.

These statements were made by:

**Chemical Check GmbH, Wöbbeler Straße 2-4, D-32839 Steinheim, Tel.: +49 5233 94 17 0, +49 1805-CHEMICAL / +49 180 52 43 642, Fax: +49 5233 94 17 90, +49 180 50 50 455**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.