

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### Identification of the substance or preparation

**HYDRO-STÖSSEL-ADDITIV 300ML**

**Art.: 1009**

#### Use of the substance/preparation

Additives

#### Company/undertaking identification

LIQUI MOLY GmbH, Jerg-Wieland-Straße 4, D-89081 Ulm-Lehr  
 Telephone (+49) 0731-1420-0, Fax (+49) 0731-1420-88

E-mail address of the competent person: info@chemical-check.de, k.schnurbusch@chemical-check.de

#### Emergency telephone

#### Advisory office in case of poisoning:

Tel.:

#### Telephone number of the company in case of emergencies:

Tel. (+49) 0731-1420-0

### 2. HAZARDS IDENTIFICATION

#### To people

See point 11 and 15.

Preparation is not classified as hazardous in the sense of directive 1999/45/EC.

#### To the environment

See point 12.

Product can compose a film on the water surface, which can prevent oxygen exchange.

### REGULATION (EC) No 648/2004

30 % and more  
 aliphatic hydrocarbons  
 15 % or over but less than 30 %  
 aromatic hydrocarbons

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	Symbol	R-phrases	EINECS, ELINCS
content %	Registration number (ECHA)		

--	---	---	

### 4. FIRST AID MEASURES

#### 4.1 Inhalation

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision: 30.07.2009 Replaces the version of: 04.02.2009 PDF date: 30.07.2009  
HYDRO-STÖSSEL-ADDITIV 300ML Art.: 1009

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.

#### **4.2 Eye contact**

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.  
Keep Data Sheet available.

#### **4.3 Skin contact**

Wash thoroughly with soap and copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

#### **4.4 Ingestion**

Rinse the mouth thoroughly with water.  
Do not induce vomiting. Consult doctor immediately.

#### **4.5 Special resources necessary for first aid**

Indications for the physician:  
Symptomatic treatment

### **5. FIRE-FIGHTING MEASURES**

#### **5.1 Suitable extinguishing media**

Water jet spray/foam/CO<sub>2</sub>/dry extinguisher  
Cool container at risk with water.

#### **5.2 Extinguishing media which shall not be used for safety reasons**

High volume water jet

#### **5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases**

In case of fire the following can develop:

Oxides of carbon  
Toxic pyrolysis products.  
Hot product gives off combustible vapours.

#### **5.4 Special protective equipment for fire-fighters**

Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary

#### **5.5 Further information**

Dispose of contaminated extinction water according to official regulations.

### **6. ACCIDENTAL RELEASE MEASURES**

Refer to point 13. and for personal protection refer to point 8.

#### **6.1 Personal precautions**

Ensure sufficient supply of air.  
Avoid formation of oil mist.  
Avoid contact with eyes or skin.  
If applicable, caution - risk of slipping  
Do not carry cleaning cloths soaked in product in trouser pockets.

#### **6.2 Environmental precautions**

If leakage occurs, dam up.  
Prevent from entering drainage system.  
Prevent surface and ground-water infiltration, as well as ground penetration.  
If accidental entry into drainage system occurs, inform responsible authorities.

#### **6.3 Methods for cleaning up**

Collect using absorbant material (e.g. Universal binding medium), and dispose of according to point 13.

### **7. HANDLING AND STORAGE**

#### **7.1 Handling**

##### **Tips for safe handling:**

See point 6.1  
Ensure good ventilation.  
General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.

GB

3 / 6  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision: 30.07.2009 Replaces the version of: 04.02.2009 PDF date: 30.07.2009  
 HYDRO-STÖSSEL-ADDITIV 300ML Art.: 1009

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.  
 Do not heat to temperatures close to flash point.

## 7.2. Storage

### Requirements for storage rooms and containers:

Not to be stored in gangways or stair wells.  
 Store product closed and only in original packing.  
 Do not store with oxidizing agents.  
 Solvent resistant floor

### Special storage conditions:

See point 10  
 Protect against moisture and store closed.  
 Store in a well ventilated place.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Exposure limit values

GB	Chemical Name	Baseoil - unspecified	Content %:
	WEL-TWA: 300 mg/m3 (AGW)	WEL-STEL: 2(II) (AGW)	---
	BMGV: ---	Other information: ---	
GB	Chemical Name	Oil mist, mineral	Content %:
	WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH)	---
	BMGV: ---	Other information: ---	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

### 8.2 Exposure controls

#### 8.2.1 Occupational exposure controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Respiratory protection:  
 Normally not necessary.  
 With oil mist formation:  
 Filter A2 P2 (EN 14387)  
 Hand protection:  
 Protective gloves, oil resistant (EN 374)  
 If applicable  
 Protective Neopren gloves (EN 374).  
 Protective nitrile gloves (EN 374)  
 Protective hand cream recommended.  
 Eye protection:  
 Tight fitting protective goggles (EN 166) with side protection, with danger of projections.  
 Skin protection:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Additional information on hand protection - No tests have been performed.  
 Selection made for preparations according to the best available knowledge and information on the ingredients.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision: 30.07.2009 Replaces the version of: 04.02.2009 PDF date: 30.07.2009  
 HYDRO-STÖSSEL-ADDITIV 300ML Art.: 1009

and varies from manufacturer to manufacturer.

In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

## 8.2.2 Environmental exposure controls

n.av.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Colour:	Light brown
Odour:	Characteristic
pH-value undiluted:	n.a.
Boiling point/boiling range (°C):	n.av.
Melting point/melting range (°C):	n.av.
Flash point (°C):	n.c.
Autoflammability:	n.c.
Oxidising properties:	No
Minimum limit of explosion:	n.a.
Maximum limit of explosion:	n.a.
Vapour pressure:	n.c.
Density (g/ml):	0,887 g/cm <sup>3</sup> (20°C)
Water solubility:	Insoluble
Viscosity:	1100 mPas (20°C)

## 10. STABILITY AND REACTIVITY

### Conditions to avoid

See point 7

Stable when handled and stored correctly.

Strong heat

### Materials to avoid

See point 7

Avoid contact with strong oxidizing agents.

### Hazardous decomposition products

See point 5.3

No decomposition when used as directed.

## 11. TOXICOLOGICAL INFORMATION

### Acute toxicity and immediate effects

Ingestion, LD50 rat oral (mg/kg):	n.av.
Inhalation, LC50 rat inhal.(mg/l/4h):	n.av.
Skin contact, LD50 rat dermal (mg/kg):	n.av.
Eye contact:	n.av.

### Delayed and chronic effects

Sensitization:	n.c.
Carcinogenicity:	n.c.
Mutagenicity:	n.c.
Reproductive toxicity:	n.c.
Narcosis:	n.c.

### Further information

No classification according to calculation procedure.

The following may occur:

With long-term contact:

Product removes fat.

Drying of the skin.

Dermatitis (skin inflammation)

## 12. ECOLOGICAL INFORMATION

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision: 30.07.2009 Replaces the version of: 04.02.2009 PDF date: 30.07.2009  
 HYDRO-STÖSSEL-ADDITIV 300ML Art.: 1009

Water hazard class (Germany):	1
Self classification:	Yes (VwVwS)
Persistence and degradability:	
Potentially biologically degradable:	
According to the recipe, contains no AOX.	
Behaviour in sewage plants:	Mechanical precipitation possible.
Aquatic toxicity:	n.av.
Ecological toxicity:	n.av.

### 13. DISPOSAL CONSIDERATIONS

#### 13.1. for the material / preparation / residue

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.  
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.  
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)  
 13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Pay attention to local and national official regulations

Implement substance recycling.

E.g. suitable incineration plant.

Ask manufacturer about possibility of returning residue.

#### 13.2 for contaminated packing material

See point 13.1

Pay attention to local and national official regulations

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

### 14. TRANSPORT INFORMATION

#### General statements

UN-Number: n.a.

#### Road/Rail-transport (ADR/RID)

Class/packing group: n.a.

Classification code: n.a.

LQ: n.a.

Tunnel restriction code:

#### Transport by sea

IMDG-code: n.a. (class/packing group)

Marine Pollutant: n.a.

#### Transport by air

IATA: n.a. (class/secondary danger/packing group)

#### Additional information:

Non-dangerous material according to Transport Regulations.

### 15. REGULATORY INFORMATION

#### Classification according to Dangerous Product Regulations incl. EC Directives (67/548/EEC and 1999/45/EC)

Symbols: Not applicable

Indications of danger: --

R-phrases:

S-phrases:

Additions: n.a.

Observe restrictions: n.a.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision: 30.07.2009 Replaces the version of: 04.02.2009 PDF date: 30.07.2009  
HYDRO-STÖSSEL-ADDITIV 300ML Art.: 1009

## 16. OTHER INFORMATION

These details refer to the product as it is delivered.

Storage class VCI (Germany):

10/12

Revised points:

3, 9, 15

### Legend:

n.a. = not applicable / n.v., k.D.v. = n.av. = not available / n.g. = n.c. = not checked

WEL = Workplace Exposure Limit EH40, TWA = Long-term exposure limit (8-hour TWA (= time weighted average) reference period), STEL = Short-term exposure limit (15-minute reference period) / BMGV = Biological monitoring guidance value EH40

AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany) / BGW = "Biologischer Grenzwert" (biological limit value, Germany)

VbF = Regulations for flammable liquids (Austria)

WGK = water hazard class (Germany) - WGK 3 = very hazardous, WGK 2 = hazardous, WGK 1 = slightly hazardous to water

VOC = Volatile organic compounds / AOX = Adsorbable organic halogen compounds

VwVwS = Administrative Order relating to substances hazardous to water (Germany)

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Wöbbeler Straße 2-4, D-32839 Steinheim, Tel.: +49 5233 94 17 0, +49 1805-CHEMICAL / +49 180 52 43 642, Fax: +49 5233 94 17 90, +49 180 50 50 455**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.