

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### Identification of the substance or preparation

**OIL ADDITIV 125ML**

**Art.: 1011**

#### Use of the substance/preparation

Lubricant

#### Company/undertaking identification

LIQUI MOLY GmbH, Jerg-Wieland-Straße 4, D-89081 Ulm-Lehr  
 Telephone (+49) 0731-1420-0, Fax (+49) 0731-1420-88

E-mail address of the competent person: info@chemical-check.de, k.schnurbusch@chemical-check.de

#### Emergency telephone

#### Advisory office in case of poisoning:

Tel.:

#### Telephone number of the company in case of emergencies:

Tel. (+49) 0731-1420-0

### 2. HAZARDS IDENTIFICATION

#### To people

See point 11 and 15.

Preparation is not classified as hazardous in the sense of directive 1999/45/EC.

#### To the environment

See point 12.

Product can compose a film on the water surface, which can prevent oxygen exchange.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name			
content %	Symbol	R-phrases	EINECS, ELINCS
	Registration number (ECHA)	DNEL	PNEC
--			

### 4. FIRST AID MEASURES

#### 4.1 Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

#### 4.2 Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### 4.3 Skin contact

Wash thoroughly with soap and copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision: 04.06.2008 Replaces the version of: 22.07.2003 PDF date: 06.06.2008  
OIL ADDITIV 125ML Art.: 1011

#### 4.4 Ingestion

Rinse the mouth thoroughly with water.  
Do not induce vomiting - give copious water to drink. Consult doctor immediately.

#### 4.5 Special resources necessary for first aid

Indications for the physician:  
Symptomatic treatment

### 5. FIRE-FIGHTING MEASURES

#### 5.1 Suitable extinguishing media

CO<sub>2</sub>  
Dry extinguisher  
Foam  
Cool container at risk with water.

#### 5.2 Extinguishing media which shall not be used for safety reasons

High volume water jet

#### 5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In case of fire the following can develop:

Oxides of carbon  
Oxides of sulphur  
Toxic pyrolysis products.  
Hot product gives off combustible vapours.

#### 5.4 Special protective equipment for fire-fighters

Protective respirator with independent air supply  
According to size of fire  
Full protection, if necessary

#### 5.5 Further information

Dispose of contaminated extinction water according to official regulations.

### 6. ACCIDENTAL RELEASE MEASURES

Refer to point 13. and for personal protection refer to point 8.

#### 6.1 Personal precautions

Ensure sufficient supply of air.  
Avoid formation of oil mist.  
Avoid contact with eyes or skin.  
If applicable, caution - risk of slipping.  
Do not carry cleaning cloths soaked in product in trouser pockets.

#### 6.2 Environmental precautions

If leakage occurs, dam up.  
Prevent from entering drainage system.  
Prevent surface and ground-water infiltration, as well as ground penetration.

#### 6.3 Methods for cleaning up

Collect using absorbant material (e.g. Universal binding medium), and dispose of according to point 13.

### 7. HANDLING AND STORAGE

#### 7.1 Handling

##### Tips for safe handling:

See point 6.1  
Ensure good ventilation.  
Do not heat to temperatures close to flash point.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Wash hands before breaks and at end of work.  
General hygiene measures for the handling of chemicals are applicable.  
Observe directions on label and instructions for use.

#### 7.2. Storage

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision: 04.06.2008 Replaces the version of: 22.07.2003 PDF date: 06.06.2008  
 OIL ADDITIV 125ML Art.: 1011

## Requirements for storage rooms and containers:

Store product closed and only in original packing.  
 Not to be stored in gangways or stair wells.  
 Solvent resistant floor  
 Do not store with oxidizing agents.

## Special storage conditions:

See point 10  
 Store in a well ventilated place.  
 Protect from direct sunlight and warming.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Exposure limit values

Chemical Name	Oil mist, mineral	Content %:	
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH)	---	
BMGV: ---	Other information: ---		
Chemical Name	Baseoil - unspecified	Content %:	
WEL-TWA: 300 mg/m3 (AGW)	WEL-STEL: 2(II) (AGW)	---	
BMGV: ---	Other information: ---		
Chemical Name	Molybdenum disulphide	Content %:	
WEL-TWA: 10 mg/m3 (molybdenum insoluble compounds, as Mo)	WEL-STEL: 20 mg/m3 (molybdenum insoluble compounds, as Mo)	---	
BMGV: ---	Other information: ---		

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

### 8.2 Exposure controls

#### 8.2.1 Occupational exposure controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Respiratory protection:

Normally not necessary.

With oil mist formation

Filter A P 3 (EN 141)

Hand protection:

Protective gloves, oil resistant (EN 374)

If applicable

Protective nitrile gloves (EN 374)

Protective Neopren gloves (EN 374).

Protective hand cream recommended.

Eye protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection:

Protective working garments (e.g. safety shoes EN 344, long-sleeved protective working garments)

Additional information on hand protection - No tests have been performed.

Selection made for preparations according to the best available knowledge and information on the ingredients.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of preparations the resistance of glove materials cannot be calculated in advance

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision: 04.06.2008 Replaces the version of: 22.07.2003 PDF date: 06.06.2008  
 OIL ADDITIV 125ML Art.: 1011

so it has to be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

## 8.2.2 Environmental exposure controls

n.av.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Colour:	Black
Odour:	Characteristic
pH-value undiluted:	n.a.
Boiling point/boiling range (°C):	n.av.
Melting point/melting range (°C):	n.av.
Flash point (°C):	201
Oxidising properties:	No
Minimum limit of explosion:	n.a.
Maximum limit of explosion:	n.a.
Vapour pressure:	n.c.
Density (g/ml):	0,9 (20°C)
Water solubility:	Insoluble
Vapour density (air = 1):	n.c.
Viscosity:	95 mm <sup>2</sup> /s (40°C)

## 10. STABILITY AND REACTIVITY

### Conditions to avoid

See point 7  
 Stable when handled and stored correctly.  
 Strong heat

### Materials to avoid

See point 7  
 Avoid contact with strong oxidizing agents.

### Hazardous decomposition products

See point 5.3

## 11. TOXICOLOGICAL INFORMATION

### Acute toxicity and immediate effects

Ingestion, LD50 rat oral (mg/kg):	n.av.
Inhalation, LC50 rat inhal.(mg/l/4h):	n.av.
Skin contact, LD50 rat dermal (mg/kg):	n.av.
Eye contact:	n.av.

### Delayed and chronic effects

Sensitization:	n.c.
Carcinogenicity:	n.c.
Mutagenicity:	n.c.
Reproductive toxicity:	n.c.
Narcosis:	n.c.

### Further information

No classification according to calculation procedure.  
 The following may occur:  
 With long-term contact:  
 Product removes fat  
 Drying of the skin.  
 Dermatitis (skin inflammation)

## 12. ECOLOGICAL INFORMATION

Water hazard class (Germany):	2
Self classification:	Yes (VwVwS)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision: 04.06.2008 Replaces the version of: 22.07.2003 PDF date: 06.06.2008  
 OIL ADDITIV 125ML Art.: 1011

Persistence and degradability:	Potentially biologically degradable.
Behaviour in sewage plants:	Mechanical precipitation possible.
According to the recipe, contains no AOX.	
Aquatic toxicity:	n.av.
Ecological toxicity:	n.av.

## 13. DISPOSAL CONSIDERATIONS

### 13.1. for the material / preparation / residue

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.  
 EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.  
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)  
 13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Pay attention to local and national official regulations  
 Implement substance recycling.  
 E.g. suitable incineration plant.

### 13.2 for contaminated packing material

See point 13.1

Pay attention to local and national official regulations

Empty container completely.

Untampered packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## 14. TRANSPORT INFORMATION

### General statements

UN-Number: n.a.

### Road/Rail-transport (ADR/RID)

Class/packing group: n.a.

Classification code: n.a.

LQ: n.a.

### Transport by sea

IMDG-code: n.a. (class/packing group)

Marine Pollutant: n.a.

### Transport by air

IATA: n.a. (class/secondary danger/packing group)

### Additional information:

Non-dangerous material according to Transport Regulations.

## 15. REGULATORY INFORMATION

### Classification according to Dangerous Product Regulations incl. EC Directives (67/548/EEC and 1999/45/EC)

Symbols: Not applicable

Indications of danger: ---

R-phrases:

S-phrases:

Additions: n.a.

Observe restrictions: n.a.

VOC 1999/13/EC k.D.v.

## 16. OTHER INFORMATION

These details refer to the product as it is delivered.

Storage class VCI (Germany):

10/12

Revised points:

1 - 16 (REACH)

### Legend:

n.a. = not applicable / n.v., k.D.v. = n.av. = not available / n.g. = n.c. = not checked

WEL = Workplace Exposure Limit EH40, TWA = Long-term exposure limit (8-hour TWA (= time weighted average) reference period), STEL = Short-term exposure limit (15-minute reference period) / BMGV = Biological monitoring guidance value EH40

AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany) / BGW = "Biologischer Grenzwert" (biological limit value, Germany)

VbF = Regulations for flammable liquids (Austria)

WGK = water hazard class (Germany) - WGK 3 = very hazardous, WGK 2 = hazardous, WGK 1 = slightly hazardous to water

VOC = Volatile organic compounds / AOX = Adsorbable organic halogen compounds

VwVwS = Administrative Order relating to substances hazardous to water (Germany)

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Wöbbeler Straße 2-4, D-32839 Steinheim, Tel.: +49 5233 94 17 0, +49 1805-CHEMICAL / +49 180 52 43 642, Fax: +49 5233 94 17 90, +49 180 50 50 455**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.